

Technical Sales Sheet

Solvitol Copper Anti-Seize Spray

Description

Solvitol Copper Anti-Seize (HTLC) has been specially designed for use during the assembly of threaded or other components where protection against oxidation, corrosion or chemical attack is required both at ambient and high temperatures.

Applications

It can be used on all types of components, including threads, pins, valve stems, etc. and a wide range of materials including austenitic stainless steel.

Benefits

- * Prevents seizure.
- * Prevents corrosion.
- * Prevents damaged threads.
- * Assists assembly.
- * Wide temperature range.
- * Resists chemical attack.
- * Easy to apply spray application.
- * Available in a 400ml aerosol.

Technical Data

Appearance	: Dark copper.
Contents	: No lead, silicones or chlorinated solvents.
Temperature range	: -15°C to 1100°C
Water solubility	: Insoluble.
Carrier	: Non-melting grease.
Consistency	: Soft grease

Pack Sizes: -

Aerosol 12 x 400ml box

Directions for Use

- Aerosol - Shake can before use and spray from a distance of 15- 30cm (6 – 12 inches)
Caution - Ensure adequate ventilation.

Health and Safety

Health & Safety Information is available from the Sales Department of: -
Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.