

Technical Sales Sheet

Solvitol Cold Galvanising Spray for Steelwork

Description

Solvitol "Cold Galvanising Spray" (GLV) is a specially formulated paint primer for use on steelwork

Applications

It is designed as a primer, which prevents the corrosion taking place that would otherwise happen on unprotected steelwork. The aluminium base gives similar protection and finish to that of zinc galvanised steel.

Benefits

- * Excellent Adhesion
- * Quick Drying
- * Prevents Corrosion
- * Available in a 400ml aerosol

Technical Data

Appearance	:	Light Silver Coating
Contents	:	Aluminium powder, resins and dichloromethane
Storage	:	Below 50 degrees C
Flash Point	:	<0 degrees C

Pack Sizes: -

Aerosol 12 x 400ml box

Directions for Use

Shake can until agitator ball can be heard moving freely and then for a further 1-2 minutes. Remove excess rust and ensure that the surface to be treated is clean and dry. Apply by a series of light coats to build up to the required thickness.

Health and Safety

Health & Safety Information is available from the Sales Department of: -
Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.