

Technical Sales Sheet

Solvitol Dry Film Lubricant Spray

Description

Solvitol Dry Film Lubricant (DFL) is a specially formulated dry lubricant for use where conventional oils are not suitable.

Applications

Solvitol Dry Film Lubricant effectively replaces conventional oils and greases where dry lubrication is required. It is suitable for use on machine slides and moulds and is effective up to 350 degrees C.

Benefits

- * Dry lubricant.
- * Durable coating containing Molybdenum Disulphide.
- * Working temperature up to 350 degrees C.
- * Anti static properties.
- * Water and chemical resistant.
- * Easy to apply spray application.
- * Available in a 400ml aerosol.

Technical Data

Appearance	:	Black durable coating.
Contents	:	Molybdenum disulphide, resin binder and chlorinated hydrocarbon solvent blend.
Temperature range	:	Up to 350 degrees C
Flashpoint	:	Propellant -40 degrees C, product is non flammable.

Pack Sizes: -

Aerosol 12 x 400ml box

Directions for Use

Aerosol - Spray from 6- 9 inches on to a clean dry surface. Coating will be touch dry in 5 minutes and will be ready to use in 15 minutes.

Health and Safety

Health & Safety Information is available from the Sales Department of: -
Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.