

Technical Sales Sheet

Solvitol Graphited Penetrating Oil

Description

Solvitol Graphited Penetrating Oil (GPO) is a specially formulated lubricant offering excellent penetrating and release properties.

Applications

It is designed to be used to release rusted, seized and corroded nuts, bolts, hinges, locks, linkages, tools and fittings etc. It is also suitable for cleaning and the removal of rust. The addition of graphite prevents seizure enabling easier release once initial freeing has occurred.

Benefits

- * Effective Penetration
- * Graphite Residue ensures excellent lubrication
- * Removes Rust
- * Cleans
- * Ozone Friendly

Technical Data

Appearance	:	Grey/ black liquid
Contents	:	Combination of aliphatic hydrocarbons, mineral oil, graphite powder and hydrocarbon propellant.
Storage	:	Store away from direct sunlight
Flash Point	:	<0 Degrees C

Pack Sizes: -

Aerosol 400ml

Directions for Use

Shake can well before use. Spray on to part from a distance of 6-9 inches. Allow a few minutes for the product to penetrate before disassembly.

Health and Safety

Health & Safety Information is available from the Technical Service Department of: -
Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.