

Technical Sales Sheet

Solvitol Leak Detector Spray

Description

Solvitol Leak Detector Spray has been developed to locate gas leaks on equipment during use or after assembly prior to commissioning.

Applications

Solvitol Leak Detector produces a micro stable foam which will indicate the position of the smallest gas leak. It can be used on Oxy- Acetylene and LPG (Butane/ Propane) and will not form a combustible mixture with other gases. It is ideal for use by welders, plumbers and gas fitters.

Benefits

- * Not classified as flammable.
- * Non corrosive.
- * Ozone friendly.
- * Bio-degradable.
- * Easy to apply spray application.
- * Available in a 300ml aerosol.

Technical Data

Appearance	:	Opaque milky viscous liquid.
Contents	:	Blend of surface active agents and a corrosion prevention package in demineralised water, propelled by nitrogen.
Flashpoint	:	>61 degrees C

Pack Sizes: -

Aerosol 12 x 300ml box

Directions for Use

Aerosol - Spray on to suspected area of leak. A stream of bubbles will locate the exact position of the gas escape.

Caution - Do not use with phosphorous or phosphorous compound gases.

Health and Safety

Health & Safety Information is available from the Sales Department of: -
Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.

6/04