

Technical Sales Sheet

Solvitol Matt Black Paint Spray

Description

Solvitol Matt Black Paint (MBP) is formulated for use as an automotive paint.

Applications

Solvitol Matt Black Paint offers effective coverage and a quality surface finish when used as directed.

Benefits

- * Professional finish.
- * Matt finish.
- * Excellent opacity.
- * Easy to apply spray application.
- * Available in a 400ml aerosol.

Technical Data

Appearance	:	Opaque black liquid drying to leave a matt finish.
Contents	:	Blend of polyurethane resin pigment, drying modifiers, acetone, Xylene and hydrocarbon propellant.
Flashpoint	:	<0 degrees C

Pack Sizes: -

Aerosol 12 x 400ml box

Directions for Use

Aerosol - Remove rust and loose flaking paint with a wire brush. Smooth off with wet and dry paper. Finished surface should be free from oil and grease.

Shake aerosol for 3 minutes then spray from a distance of 10- 15 inches using smooth, even strokes. Allow to touch dry before applying further coats. Avoid spraying in damp conditions.

Always invert the can after use and spray to clear the valve and nozzle.

Health and Safety

Health & Safety Information is available from the Sales Department of: -

Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.

6/04