

Technical Sales Sheet

Solvitol Open Gear and Wire Rope Lubricant Spray

Description

Solvitol Open Gear and Wire Rope Lubricant (OGL) is specially formulated to offer effective lubrication of gears and wire ropes.

Applications

Solvitol Open Gear and Wire Rope Lubricant is ideal for the economical lubrication and protection of gears sliding surfaces and wire ropes. All forms of machinery in manufacturing industries, crane and plant hire, mines, and quarries, council departments, shipyards and the construction industry can be maintained with this product.

Benefits

- * Good adhesion to metal surfaces.
- * Will not throw off running gears.
- * Protects against corrosion.
- * Penetrates inaccessible areas.
- * Water and chemical resistant.
- * Prolongs component life.
- * Prevents seizure.
- * Easy to apply spray application.
- * Available in a 400ml aerosol.

Technical Data

Appearance	: Dark viscous lubricant.
Contents	: Blend of hydrocarbon oil derivatives, anti fling and extreme pressure additives and hydrocarbon propellant.
Flashpoint	: <0 degrees C

Pack Sizes: -

Aerosol 12 x 400ml box

Directions for Use

Aerosol - Apply directly to the surface requiring lubrication using the extension tube to reach inaccessible areas if necessary.

Health and Safety

Health & Safety Information is available from the Sales Department of: -
Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.