

Technical Sales Sheet

Solvitol P.T.F.E. Spray

Description

Solvitol P.T.F.E. Spray (PTFED) is designed to provide a dry film, low friction surface. It also has excellent non-stick, non-staining properties with a wide temperature range.

Applications

Solvitol P.T.F.E. Spray can be used on a very wide range of materials including rubber, wood, plastics, metal etc.

Benefits

- * Dry film lubricant
- * Excellent low load capability
- * Wide temperature range
- * Safe to use
- * Non-staining
- * Easy to apply spray application.
- * Available in a 400ml aerosol

Technical Data

Appearance : Slight white deposit
Odour : Mild
Temperature range : Up to 250°C

Pack Sizes: -

Aerosol 12 x 400ml box

Directions for Use

Shake can well before use and spray from a distance of 15-30cs (6-12 inches).

Health and Safety

Health and Safety information is available from the Sales Department of:- Solvitol Limited, Portobello Industrial Estate, Birtley, Co. Durham DH3 2RE. Fax 0191 492 0503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy itself that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited's conditions of sale which are hereby incorporated into this bulletin. No liability can be assumed by Solvitol Limited for the information given.