

Technical Sales Sheet

Solvitol Penetrant Spray & Fluid

Description

Solvitol Penetrant Spray (CPO) is specially formulated to give rapid penetration and effective release of rusted and seized components.

Applications

It can be used on all types of components, including threads, pins, valve stems, etc. where disassembly is found to be a problem.

Benefits

- * Rapid penetration.
- * Excellent release properties.
- * Reduces break loose torque.
- * Allows rapid dismantling.
- * Prevents corrosion.
- * Displaces water.
- * Easy to apply spray application.
- * Available in a 400ml aerosol.

Technical Data

Appearance	:	Light amber.
Odour	:	Mild.
Contents	:	No silicones or chlorinated solvents.
Low Temp Stability	:	Excellent.
Temperature Range	:	0°C to + 85°C
Aerosol	:	Extension nozzle.

Pack Sizes: -

Aerosol 12 x 400ml box

Directions for Use

- Aerosol - Shake can before use and spray from a distance of 15- 30cm (6 – 12 inches)
Caution - Ensure adequate ventilation.

Health and Safety

Health & Safety Information is available from the Sales Department of: -
Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.