

# Technical Sales Sheet

## Solvitol Solvent Based Spatter Release Spray

### Description

Solvitol Solvent Based Spatter Release Spray (WSR) has been specifically designed to prevent the adhesion of weld spatter to work surfaces, nozzles, jigs, fixtures, etc. It is not classified as flammable, economical in use, and will not affect the weld formation.

### Applications

It can be used on all types of welding operations including MIG, and CO2, as well as robotics.

### Benefits

- \* Not classified as flammable.
- \* Economical in use.
- \* Prevents adhesion.
- \* Long lasting.
- \* Spatter easily removed.
- \* Does not affect weld.
- \* Easy to apply spray application.
- \* Available in a 450grm aerosol

### Technical Data

Appearance : Light amber liquid.  
Contents : Dichloromethane, No silicones.  
Storage : Below 30°C

### Pack Sizes: -

Aerosol 12 x 450grm box

### Directions for Use

Shake the can before use; hold upright and spray from a distance of 15- 30cm (6 -12 inches) apply a thin even coating.

Caution: - Ensure adequate ventilation during application.

### Health and Safety

Health & Safety Information is available from the Sales Department of: -  
Solvitol Ltd. Portobello Industrial Estate, Birtley, Co. Durham. DH3 2RE. Fax 01914920503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.

6/04