

# Technical Sales Sheet

## Solvitol Temporary Line and Spotmarking System

### Description

Solvitol Temporary Line and Spot marking system (TLM) is an aerosol packed product, which can be used in conjunction with a manually wheeled applicator for line marking or independently for spot marking. It is a fast drying, water based emulsion polymer system designed for use by contractors and other users that require a temporary, easily removed, fast drying line or spot marking system. Solvitol Temporary Linemarking Paint is available in eight colours – white, yellow, red, green, blue, grey, black and orange. Each aerosol will produce approximately 75-100 metres of line 50mm in width.

### Applications

Solvitol Temporary Linemarker is designed to be used by contractors etc., for marking out areas using different colour codes to denote the activity. It can also be used in the same way for car parks, warehouses, factories, recreation facilities and school playgrounds where an easily removed paint is required.

### Benefits

- \* Easy to apply.
- \* Fast drying.
- \* Guaranteed not to clog.
- \* UV Stable.
- \* Easily removed with detergent and water.
- \* Spot marking capability.
- \* Compatible with most linemarking applicators. (hand applied, 2 and 4 wheel trolleys available on request)
- \* Available in 750ml aerosols.

### Technical Data

Appearance	:	Coloured paint
Odour	:	Characteristic paint aroma
Touch dry	:	10-15 minutes
Full cure	:	2- 3 hours

### Pack Sizes: -

Aerosol 12 x 750ml box

### Directions for Use

Solvitol Temporary Linemarker aerosols are designed for use with the Temporary Linemarker applicator for line marking or independently for Spot marking.

Ensure that the surface to be painted is dry, clean and free from oil, grease, grime and dirt.

Shake the can vigorously for 1-2 minutes until the agitator balls are rattling freely. Fit nozzle to the upright can. Invert the can and fit in the applicator.

Press the trigger on the applicator whilst moving forward. The speed of movement controls the density of the line. After use, clear the nozzle by spraying the can in the upright position.

### Health and Safety

Health and Safety information is available from the Sales Department of: - Solvitol Limited, Portobello Industrial Estate, Birtley, Co. Durham DH3 2RE. Fax 0191 492 0503

Where tolerances are not stated, figures are typical of normal production. Whilst every care is taken to ensure the accuracy of the material contained in the bulletin, the technical data is provided for information only. The buyer shall use its own skill and judgement to satisfy it that the products are suitable for the buyer's purposes. The entire liability of Solvitol Limited in relation to the products shall be set out in Solvitol Limited conditions of sale, which are hereby incorporated into this bulletin. Solvitol Limited can assume no liability for the information given.